

Batten Light



BATTEN LIGHT RANGE



- Replacable light source batten light design
- Strong steel housing with anti corrosion coating
- High luminous efficiency T8 light source
- Compliance with CE and Rohs standards

T8 Batten Fittings



Figure 22.1

- Legend pro series LED batten with powder coated housing and high lumen T8 light source accomplished with a luxury ambience
- Elegantly designed tube light in glass body for efficient light output



220-240 VOLTAGE	100lm/WATTS
0.0%	IP 20
25000 HOURS	ON OFF ≥1250
Hz 50/60 HZ	120°
Ra ≥80	P.F. >0.5
NOT DIMMABLE	<1 se



CCT — 3000K 4000K 6000K

T8 Batten Frame



Figure 22.2

- High quality material and static powder coated finish conforms to IEC standard
- Easy installation
- Modern twist type safety lamp holders
- Suitable for G13 LED Tube



220-240 VOLTAGE	90lm/WATTS
0.0%	IP 20
25000 HOURS	ON OFF ≥1250
Hz 50/60 HZ	120°
Ra ≥80	P.F. >0.5
NOT DIMMABLE	<1 se

CCT — 3000K 4000K 6000K

Model	Watts	Voltage	P.F	Lumen	Dimension(mm)	Base	Image Code
BFB110/LTX	10W	175-240V	>0.5	100lm/w	622X70	G13	Figure 22.1
BFB120/LTX	20W	175-240V	>0.5	100lm/w	1230X70	G13	Figure 22.1
BFB220/LTX	40W	175-240V	>0.5	100lm/w	1230x70	G13	Figure 22.1
BF4/LTX	MAX ≤ 100W	220-240V	>0.5	-	1230X68	G13	Figure 22.2
BF4X2/LTX	MAX ≤ 100W	220-240V	>0.5	-	1230X68	G13	Figure 22.2
BF2/LTX	MAX ≤ 100W	220-240V	>0.5	-	622X45	G13	Figure 22.2