

| Ceiling Light



CEILING LIGHT RANGE



- Modern slim design IP44 & IP65 range
- High quality poly carbonate material
- High luminous efficiency and long life span
- Compliance with CE and CB standards

Ceiling Light



Figure 29.1

- Ceiling mounted LED luminaires
- The simple and robust white opal diffuser allows the luminaire to cast a uniform light
- IP44 rating ensuring is safe for installing in bathroom areas



220-240 VOLTAGE	80lm/WATTS
0.0%	IP 44
25000 HOURS	ON OFF ≥1250
Hz 50/60 HZ	130°
Ra ≥80	P.F. >0.5
NOT DIMMABLE	<1 se



CCT — 3000K 4000K 6000K

Ceiling Light



Figure 29.2

- IP65 range Ceiling mounted LED luminaires
- Solid structure and high efficiency light source & anti corrosion PC diffuser
- The opal diffuser structure optimises light output, simultaneously reducing damaging glare



220-240 VOLTAGE	90lm/WATTS
0.0%	IP 65
25000 HOURS	ON OFF ≥1250
Hz 50/60 HZ	120°
Ra ≥80	P.F. >0.9
NOT DIMMABLE	<1 se

CCT — 3000K 4000K 6000K

Model	Watts	Voltage	P.F	Lumen	Dimension(mm)	Install Size(mm)	Image Code
CL20/LTX	20W	220-240V	>0.5	80lm/W	290X65	200	Figure 29.1
CL24/LTX	24W	220-240V	>0.5	80lm/W	340X65	300	Figure 29.1
CL18IP65/LTX	18W	220-240V	>0.9	90lm/W	280X55	80	Figure 29.2
CL24IP65/LTX	24W	220-240V	>0.9	90lm/W	330X55	90	Figure 29.2