

## | Emergency Light



### EMERGENCY & EXIT LIGHT RANGE

---



- Multi functional installation design
- Poly carbonate housing with clear diffuser
- High output 3 hour non-maintained operation
- Compliance with CE and Rohs standards

# Emergency Light



Figure 52.1

- LED Recessed or surfaced multiple use emergency light
- High light output and 3hour non maintained operation
- Powered by high quality Ni\_cd battery



220-240 VOLTAGE	100lm/WATTS
0.0%	<b>IP</b> 40
25000 HOURS	<b>ON OFF</b> ≥1250
<b>Hz</b> 50/60 HZ	120°
<b>Ra</b> ≥80	<b>P.F.</b> >0.5
NOT DIMMABLE	<1 se



CCT — 3000K 4000K 6000K

# Emergency Light



Figure 52.2

- LED Surface mounted emergency light, Polycarbonate construction with clear diffuser
- High light outout and 3hour non maintained operation
- Powered by high quality Ni\_cd battery



220-240 VOLTAGE	100lm/WATTS
0.0%	<b>IP</b> 40
25000 HOURS	<b>ON OFF</b> ≥1250
<b>Hz</b> 50/60 HZ	120°
<b>Ra</b> ≥80	<b>P.F.</b> >0.5
NOT DIMMABLE	<1 se

CCT — 3000K 4000K 6000K

Model	Watts	Voltage	P.F	Battery	Dimension(mm)	Emergency Duration	Image Code
EL3M/LTX	3W	220-240V	>0.5	800mAh	265X105X50	3Hrs	Figure 52.1
EL4L/LTX	4W	220-240V	>0.5	1200mAh	340X105X80	3Hrs	Figure 52.2