

Spot Light



SPOT DOWNLIGHT RANGE

- Integrated spot light design
- High quality heat sink plastic material
- Perfect beam angles for every spot
- Compliance with CE and CB standards

Spot Downlight



Figure 13.1

- Solid structure design and high quality material acquired, providing higher safety level
- High quality heat dissipation design deliver more life
- Whole range replaceability to traditional ceiling light, available in different size and power

	220-240 VOLTAGE	80lm/WATTS
	0.0%	IP 40
	25000 HOURS	ON OFF ≥1250
	Hz 50/60 HZ	24°
	Ra ≥80	P.F. >0.5
	OPTIONAL DIMMABLE	<1 se

CCT — 3000K 4000K 6000K

Spot Downlight



Figure 13.2

- Anti glare design with high light quality and efficiency
- The deep seated glossy reflector with lens, result in high degree of uniform illumination besides excellent glare control

	220-240 VOLTAGE	80lm/WATTS
	0.0%	IP 40
	25000 HOURS	ON OFF ≥1250
	Hz 50/60 HZ	24°
	Ra ≥80	P.F. >0.5
	Optional DIMMABLE	<1 se

CCT — 3000K 4000K 6000K

Model	Watts	Voltage	P.F	Lumen	Dimension(mm)	Hole size(mm)	Image Code
SP7/LTX	7W	220-240V	>0.5	80lm/W	95X47	75	Figure 13.1
SP6D/LTX	6W	220-240V	>0.5	80lm/W	95X47	75	Figure 13.1
SP7A/LTX	7W	220-240V	>0.5	80lm/W	85X47	75	Figure 13.2

Spot Downlight



Figure 14.1

- Surface mounted design and high quality material acquired, providing higher safety level
- High quality heat dissipation design deliver more life
- 360° full range of adjustable lighting
- Colour finish available black & White

	220-240 VOLTAGE		80lm/WATTS
	0.0%	IP	44
	30000 HOURS	ON OFF	≥1250
	50/60 HZ		35°
	NOT DIMMABLE	Ra	≥80
	P.F.		>0.5
			<1 se

CCT — 3000K 4000K 6000K

Spot Downlight



Figure 14.2

- Solid structure design and high quality material acquired, providing higher safety level
- Aesthetically designed MR16 and GU10 lamp base
- PMMA lens for better light distribution

	220-240 VOLTAGE		80lm/WATTS
	0.0%	IP	20
	25000 HOURS	ON OFF	≥1250
	50/60 HZ		38°
	Optional DIMMABLE	Ra	≥80
	P.F.		>0.5
			<1 se

CCT — 3000K 4000K 6000K

Model	Watts	Voltage	P.F	Lumen	Dimension(mm)	Base	Image Code
CTL10WH/LTX	10W	220-240V	>0.5	90lm/W	75X100	NIL	Figure 14.1
CTL10BK/LTX	10W	220-240V	>0.5	90lm/W	75X100	NIL	Figure 14.2
MR165/LTX	5W	220-240V	>0.5	80lm/W	50X55	GU5.3	Figure 14.2
MR165GU10/LTX	5W	220-240V	>0.5	80lm/W	50X55	GU10	Figure 14.2
MR167/LTX	7W	220-240V	>0.5	80lm/W	50X55	GU5.3	Figure 14.2
MR167DIM/LTX	7W	220-240V	>0.5	80lm/W	50X55	GU5.3	Figure 14.2