

| Track Light



TRACK LIGHT RANGE


- Simple and slick integral designed track lights
- High quality di-cast aluminium housing
- High CRI and perfect beam spot light
- Compliance with CE and Rohs standards

Track Light



Figure 31.1

- Anti-glare with high lumen COB chip & PMMA lens
- Uniform lighting
- Flicker free internal driver
- Modular lens design for different angles



220-240 VOLTAGE	90lm/WATTS
0.0%	IP 40
25000 HOURS	ON OFF ≥1250
Hz 50/60 HZ	36°
Ra ≥80	P.F. >0.5
NOT DIMMABLE	<1 se


CCT — 3000K 4000K 6000K

Track Light



Figure 31.1

- Anti-glare with high lumen COB chip & PMMA lens
- Uniform lighting
- Flicker free internal driver
- Modular lens design for different angles



220-240 VOLTAGE	90lm/WATTS
0.0%	IP 40
25000 HOURS	ON OFF ≥1250
Hz 50/60 HZ	36°
Ra ≥80	P.F. >0.5
NOT DIMMABLE	<1 se

CCT — 3000K 4000K 6000K

Model	Watts	Voltage	P.F	Lumen	Dimension(mm)	Beam Angle	Image Code
LTL10/LTX	10W	220-240V	>0.5	90lm/W	105X50	36°	Figure 31.1
LTL20/LTX	20W	220-240V	>0.5	90lm/W	150X68	36°	Figure 31.1
LTL30/LTX	30W	220-240V	>0.5	90lm/W	150X75	36°	Figure 31.1